



DET NORSKE VERITAS

APPENDIX TO CERTIFICATE

This Appendix pertains to Certificate No. 1162-CPD-0341

Page 2(2)

Solna 2009-03-18

DORMA Sverige AB

EN 12209:2004 and EN 12209:2004/AC:2005

Conclusions

Lock model DL 712 and DL 912 are approved, according to EN 12209
 The locks can be used on fire/smoke approved resistant doors.
 Suitable for doors above 200 kg door mass and 15 N maximum closing force.
 Lock model DL 610 and DL 618, are approved, according to EN 12209
 The locks can be used on fire/smoke approved resistant doors.
 Suitable for doors up to 200 kg door mass and 15 N maximum closing force

*	1	2	3	4	5	6	7	8	9	10	11
Product	Category of use	Durability and load on latch bolt	Door mass and closing force	Suitability for use in fire / smoke doors	Safety	Corrosion resistance and temperature	Security and drill resistance	Field of door application	Type of key operation and locking	Type of spindle operation	Key identification
Lock DL 712	3	X	9	1	0	F	3	B	A	2	0
Lock DL 912	3	X	9	1	0	F	4	B	A	2	0
Lock DL 610	3	X	8	1	0	G	2	B	B	2	0
Lock DL 618	3	X	8	1	0	G	2	B	B	2	0

Lack of fulfilment of conditions as set out in the Certification Agreement may render this Certificate invalid.