



DECLARATION OF PERFORMANCE V-Gard™ PE 200 E

No DoPVGPE200Ev01VCL-2024-06-06

Unique identification code of the product-type:

Intended use/es: Manufacturer:

System/s of AVCP: Harmonised standard: Notified body/ies: V-Gard™ PE 200 E

PE vapour control layer, Type A **Holcim Solutions and Products EMEA**lkaroslaan 75, 1930 Zaventem, Belgium

System 3 13984:2013 No. 1136

Declared performance/s:

Essential characteristics		Performance	
		Value 200µm	Unit
Reaction to fire	EN 13501-1	E	
Watertightness	EN 1928	Pass	
Tensile strength (L/T)	EN 12311-2	≥ 100 / 100	N/50mm
Elongation (L/T)	EN 12311-2	≥ 300 / 300	%
Resistance to tear (nail shank) (L/T)	EN 12310-1	≥ 75 / 75	N
Water vapour resistance (Sd)	EN 1931	110	m
Shear strength joints	EN 12317-2	NPD	
Impact resistance	EN 12691 (A)	NPD	
Durability: water vapour resistance after artificial ageing	EN 1296 & EN 1931	Pass	
Durability: chemical resistance (alkali)	EN 1847 & EN 12311-2	Pass	_
Dangerous substances		None 1)	
NPD: No Performance Determined			

¹⁾ This product is an article as defined in article 3 of EC regulation No 1907/2006 (REACH). It contains no components which are intended to be released under normal or reasonably foreseeable conditions of use. Based on current knowledge, this product does not contain substances of very high concern as listed in Annex XIV of the REACH regulation or in the "Candidate List of Substances of Very High Concern for Authorisation" published by ECHA in concentrations above 0.1 % (w/w).

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Roshan Shrestha

Product Innovation and Technical Director Holcim Solutions and Products EMEA

Zaventem, 6/6/2024

